

TRANSPARENT MATTE FINISH POLYURETHANE FILM

Ideal for tag-less labels on shirts, scrubs, undergarments but also for creative designs.

Clear, matte polyurethane film for use on solvent and eco-solvent printers, with no tape required.

Recommended for applications on light-tone fabrics such as white or off-white!

Fashion



Promotional Items



PRODUCT DESCRIPTION

- Super matte finish printable PU
- High resolution print quality
- Soft touch, lightweight and thin vinyl
- OEKO TEX standard 100 certified
- Can be applied with or without tape
- Ideal for color gradient designs
- Suitable for baby and kids clothing

APPLICATIONS

- Very easy to print, fast drying process
- Compatible with solvent/eco solvent printers
- Printing in mirror mode
- No tape required to save in production time
- Comparable to direct to garment printing

BENEFITS

- Acrylic, cotton, and polyester
- Comfortable feel to it, very pleasant to touch
- Recommended for white or light colored textiles
- Ideal for fashion garments, and promotional items
- Compatible with TrueVis Ink from Roland

SPECIFICATIONS

COMPOSITION	AVERAGE THICKNESS	CARRIER	DIMENSIONS	CERTIFICATIONS
PU	50 micron	PET Non adhesive	<i>Standard Dimensions</i> 30" x 22 yard	OEKO-TEX Standard 100 Class 1

APPLICATION INSTRUCTIONS

APPLICATIONS	CUTTING	TEMPERATURE	PRESSURE	PEEL	TAPE
Cotton, Acrylic, Polyester and similar fabrics	Use a flex blade 45°	320°F / 160°C – 20 Sec	Medium	Cold	Not required

- STEP 1** - Program the printing and cutting of the design without rotating the images. Make sure to define the cut marks.
- STEP 2** - Remove the excess material, easy weeding.
- STEP 3** - Pre-press the garment for 5 seconds to flatten it and release any excess moisture. Position the design on the garment and press it at 320°F / 160°C for 20 seconds with medium pressure. We recommend using a silicon paper to protect the designs and textile during application.
- STEP 5** - Peel while cold.

NOTE: We highly recommend you to perform tests before launching a production.

CARE & MAINTENANCE RECOMMENDATIONS

APPLICATIONS	IRONING	TUMBLE-DRY	DRY-CLEAN
Up to 100°F / 40 °C	On reverse side only	Not recommended	Not recommended
STORAGE LIFE	STORAGE TEMPS	LIGHTING	POSITION
Up to 1 year	Dry room with 60°F-85°F / 15-30°C	Away from sunlight	Vertical position

Care and maintenance

- Always respect the garment instructions
- Follow printer manufacturers' instructions to print
- Always use official inks from printer manufacturers
- Printable media are very sensitive, handle with care
- Allow 24 hours after application before first wash
- Avoid the use of strong chemicals
- Wash inside out to extend the life of your design
- Do not use bleach